Sources of Pollutants in Urban Areas (Part 2) – Recent Sheetflow Monitoring

Robert Pitt, Roger Bannerman, Shirley Clark and Derek Williamson

Two research projects that examined source area sheetflows that were conducted in the 1990s are high-lighted in this chapter. These are a comprehensive project conducted in Birmingham, AL, as part of a project developing a control strategy for critical source areas, and a series of related projects conducted in Wisconsin as part of the DNR's efforts in calibrating the Source Loading and Management Model (SLAMM). A bibliography of recent source area monitoring activities by other researchers is also included in this chapter.

These recent projects conducted in Alabama and Wisconsin are more comprehensive than the earlier monitoring efforts described in the previous chapter. These large projects included a wide range of land uses, source sources, and pollutants, in coordinated monitoring efforts. This information complements the data presented previously.

24.1 Birmingham, Alabama, Sheetflow Monitoring

Pitt, et al. (1995) studied stormwater runoff samples from a variety of source areas under different rain conditions in Birmingham, AL. All of the samples were analyzed in filtered (0.45 μm filter) and non-filtered forms to enable

Pitt, R.E., R. Bannerman, S. Clark and D. Williamson. 2005. "Sources of Pollutants in Urban Areas (Part 2) - Recent Sheetflow Monitoring." *Journal of Water Management Modeling* R223-24. doi: 10.14796/JWMM.R223-24.
© CHI 2005 www.chijournal.org ISSN: 2292-6062 (Formerly in Effective Modeling of Urban Water Systems.
ISBN: 0-9736716-0-2)

partitioning of the toxicants into “particulate” (non-filterable) and “dissolved” (filterable) forms.

Samples were taken from shallow flows originating from homogeneous source areas by using several manual grab sampling procedures. For deep flows, samples were collected directly into the sample bottles. For shallow flows, a peristaltic hand operated vacuum pump created a small vacuum in the sample bottle, which then gently drew the sample directly into the container through a Teflon tube. About one liter of sample was needed, split into two containers: one 500 mL glass bottle with Teflon lined lid was used for the organic and toxicity analyses and another 500 mL polyethylene bottle was used for the metals and other analyses.

All samples were handled, preserved, and analyzed according to accepted protocols (EPA 1982 and 1983b). The organic pollutants were analyzed using two gas chromatographs, one with a mass selective detector (GC/MSD) and another with an electron capture detector (GC/ECD). The pesticides were analyzed according to EPA method 505, while the base neutral compounds were analyzed according to EPA method 625 (but only using 100 mL samples). The pesticides were analyzed on a Perkin Elmer Sigma 300 GC/ECD using a J&W DB-1 capillary column (30m by 0.32 mm ID with a 1 μ m film thickness). The base neutrals were analyzed on a Hewlett Packard 5890 GC with a 5970 MSD using a Supelco DB-5 capillary column (30 m by 0.25 mm ID with a 0.2 μ m film thickness). Sample extraction was critical for these organic analyses. Liquid-liquid separation funnel extractions were necessary to provide acceptably high recoveries of the organic toxicants. Burton and Pitt (2002) describe the method development for the sample handling and analyses in detail.

Metallic toxicants were analyzed using a graphite furnace equipped atomic absorption spectrophotometer (GFAA). EPA methods 202.2 (Al), 213.2 (Cd), 218.2 (Cr), 220.2 (Cu), 239.2 (Pb), 249.2 (Ni), and 289.2 (Zn) were followed in these analyses. A Perkin Elmer 3030B atomic absorption spectrophotometer was used after nitric acid digestion of the samples. Previous research (Pitt and McLean 1986; EPA 1983a) indicated that low detection limits were necessary in order to measure the filtered sample concentrations of the metals, which would not be achieved by use of a flame atomic absorption spectrophotometer, or ICP unit most commonly available in commercial laboratories. Low detection limits would enable partitioning of the metals between the solid and liquid phases to be investigated, an important factor in assessing the fates of the metals in receiving waters and in treatment processes.

Table 24.1 summarizes the source area sample data for the most frequently detected organic toxicants and for all of the metallic toxicants analyzed. The organic toxicants analyzed, but not reported, were generally detected in five, or less, of the non-filtered samples and in none of the filtered samples. Table 24.1 shows the mean, maximum, and minimum concentrations for the detected toxicants. Note that these values are based only on the observed concentrations. They do not consider the non-detectable conditions. Mean values based on total sample numbers for each source area category would therefore result in lower concentrations. The frequency of detection is therefore an important consideration when evaluating organic toxicants. High detection frequencies for the organics may indicate greater potential problems than infrequent high concentrations.

Table 24.1 stormwater toxicants detected in at least 10% of the source area sheetflow samples (Pitt, et al. 1995), is presented in the appendix at the end of this book.

Table 24.1 also summarizes the measured pH and SS concentrations. Most pH values were in the range of 7.0 to 8.5 with a low of 4.4 and a high of 11.6 for roof and concrete plant storage area runoff samples, respectively. This range of pH can have dramatic effects on the speciation of the metals analyzed. The SS concentrations were generally less than 100 mg/L, with impervious area runoff (e.g., roofs and parking areas) having much lower SS concentrations and turbidities compared to samples obtained from pervious areas (e.g., landscaped areas).

Out of more than 35 targeted organic compounds analyzed, 13 were detected in more than 10% of all samples, as shown in Table 24.1. The greatest detection frequencies were for 1,3-dichlorobenzene and fluoranthene, which were each detected in 23% of the samples. The organics most frequently found in these source area samples (i.e., polycyclic aromatic hydrocarbons (PAH), especially fluoranthene and pyrene) were similar to the organics most frequently detected at outfalls in prior studies (EPA 1983a).

Roof runoff, Roof runoff parking area and vehicle service area samples had the greatest detection frequencies for the organic toxicants. Vehicle service areas and urban creeks had several of the observed maximum organic compound concentrations. Most of the organics were associated with the non-filtered sample portions, indicating an association with the particulate sample fractions. The compound 1,3-dichlorobenzene was an exception, having a significant dissolved fraction.

In contrast to the organics, the heavy metals analyzed were detected in almost all samples, including the filtered sample portions. The non-filtered samples generally had much higher concentrations, with the exception of zinc,

which was mostly associated with the dissolved sample portion (i.e. not associated with the SS). Roof runoff generally had the highest concentrations of zinc, probably from galvanized roof drainage components, as previously reported by Bannerman, et al. (1983). Parking and storage areas had the highest nickel concentrations, while vehicle service areas and street runoff had the highest concentrations of cadmium and lead. Urban creek samples had the highest copper concentrations, which were probably due to illicit industrial connections or other non-stormwater discharges.

24.2 Source Area Pollutant Concentrations Observed in Wisconsin Urban Runoff

Described below are the source area concentrations collected in seven monitoring projects in Wisconsin, and one in Michigan. The monitoring was conducted by the United States Geological Survey (USGS) in cooperation with the Wisconsin Department of Natural Resources (WI DNR). All of the monitoring projects were conducted between 1991 and 1997. Contaminant concentrations for the source areas were used to calibrate SLAMM, the Source Loading and Management Model (Pitt and Voorhees 1995).

Madison, WI, runoff samples were collected during three months of 1991 (Bannerman, et al. 1993) to identify the relative pollutant loads from the most common source areas in two study areas. One study area was mostly residential with some commercial land use, while the second area was all light industrial land use. Sheetflow samples were collected from 46 sites representing roofs, streets, driveways, parking lots, and lawns in residential, commercial, and light industrial land uses. The sheetflow samplers were simple in design and were positioned to isolate the runoff from each type of source area. Runoff was delivered to the sample bottles by gravity and the bottles for most of the source areas were installed below the surface of the ground. An effort was made in all the projects to use sample collection methods and equipment that prevented the sample bottles from over-filling before the end of the runoff event. To a large extent, the source area concentrations represented a composite of the runoff occurring during the sampled events. Automated flow meters and water samplers were installed at the storm sewer outfalls for each study area for outfall verification. The sheetflow samples were analyzed for total suspended solids, total solids, total phosphorus, dissolved phosphorus, dissolved and total recoverable zinc, copper, cadmium, chromium, and lead, hardness, and fecal coliform bacteria.

Between 7 and 10 runoff samples were collected at all the sites, except for lawns and commercial parking areas where fewer samples were collected.

Milwaukee and Madison, WI, runoff samples were collected during 1993 (Roa-Espinosa and Bannerman 1994) to evaluate different methods for collecting source area runoff samples at industrial sites. As part of this evaluation, a total of 50 sampling locations at roofs, paved areas, and lawns were sampled at five industrial facilities. The sheetflow samplers were simple in design and they were located to isolate the runoff from each type of source area. Runoff was delivered to the sample bottles by gravity and the bottles for most of the source areas were installed below the surface of the ground. The samples were analyzed for chemical oxygen demand, suspended solids, total solids, total recoverable zinc, lead, nickel, and copper, and hardness. Depending on the location, samples were collected during 5 to 7 runoff events.

Marquette, MI, runoff samples were collected during 1993 and 1994 (Steuer, et al. 1997) to characterize contaminant concentrations for eight sources in one study area. The study area (297 acres) contained a mixture of land uses including residential, open space, commercial and institutional. A total of 33 sheetflow sampling sites were installed at streets, parking lots, driveways, rooftops, and grass areas. Samples were analyzed for total solids, suspended solids, ammonia N, nitrate plus nitrite, total Kjeldahl nitrogen, total phosphorus, dissolved phosphorus, hardness, total recoverable and dissolved zinc, lead, cadmium, and copper, fecal coliform, BOD, COD, and PAHs. Sheetflow samples were collected for 12 runoff events. Flow and water quality was measured at the storm sewer outfall for the study area.

Madison, WI, runoff samples were collected during 1994 and 1995 (Waschbusch, et al. 1999) to estimate the sources of phosphorus in two residential areas for further detailed calibration of SLAMM. All the source areas were in two drainage areas. One was 232 acres, with mostly residential and some commercial land uses, while the other was 41 residential acres. Sheetflow samples were collected from roofs, streets, driveways, parking lots, and lawns in residential and commercial land uses. Twenty five storms were sampled in both basins. The sheetflow samples were analyzed for total suspended solids, total solids, dissolved phosphorus, and total phosphorus. Flow and water quality was measured at the storm sewer outfall for both study areas.

Madison, WI, runoff samples were collected during 1994 and 1995 (Waschbusch, et al. in press) to evaluate the effect of various environmental factors on the yields of pollutants washed off city streets. The environmental factors include average daily traffic count, antecedent dry time, rainfall

intensity, rainfall depth, season, and tree canopy. Street pollutant concentrations were also used to calibrate SLAMM. Sheetflow samples were collected from five streets with different daily traffic counts. The street samplers were grouted into the street approximately 5 ft (1.5m) from the curb. The sample bottles were covered with a 6 inch (150mm) concave polycarbonate cap, set flush with the street surface. A drain hole in the cap could be constricted to control the flow into the bottle. A total of 11 or 12 runoff samples were collected for each site. Samples were analyzed for suspended solids, PAHs, hardness, and total and dissolved cadmium, lead, copper, zinc, and phosphorus.

Superior, WI, runoff samples were collected during 1995 and 1996 (Holstrom, et al. 1995 and 1996) to measure flow rates and water quality for runoff from an undeveloped site. The drainage area of the wooded lot is 76.2 acres. Flow was measured with a Parshall flume and runoff samples were collected with a volume activated water quality sampler. Sixteen storm-composite samples were analyzed for suspended solids, total solids, and total phosphorus. Samples were less frequently analyzed for COD, BOD, sulfate, chloride, nitrogen compounds, and total copper, lead, and zinc.

Madison, WI, runoff samples were collected during 1996 and 1997 (Waschbusch, et al. 1999) to verify the pollutant removal efficiency of a stormwater treatment device (Stormceptor). The device was located to treat the runoff from a 4.3 acre (1.7ha) city maintenance yard. Inlet and outlet runoff samples were collected for 45 runoff events. Samples were analyzed for total solids, suspended solids, total and dissolved phosphorus, nitrate plus nitrite, ammonia N, chloride, hardness, alkalinity, organic carbon, particle sizes, PAHs, and total and dissolved copper, cadmium, lead, and zinc. Automated sampling equipment was used to measure flow and collect flow-weighted composite samples. The inlet pollutant concentrations were used to calibrate SLAMM for industrial parking lots.

Milwaukee, WI, runoff samples were collected during 1996 (Corsi, et al. 1999) to measure the pollutant removal efficiency of a stormwater treatment device (the Multi-Chamber Treatment Train). The device was located to treat the runoff from 0.10 acres of parking lot at a city maintenance facility. Inlet and outlet samples were collected for 15 runoff events. Flow meters and automatic water samplers were used to measure flow rates and collect flow-weighted composite water samples in the inlet and outlet pipes. Samples were analyzed for total solids, suspended solids, alkalinity, BOD, COD, volatile suspended solids, ammonia as N, nitrate plus nitrite as N, chloride, sulfate, hardness, PAHs, TOC, total and dissolved phosphorus, total and dissolved

zinc, cadmium, lead, chromium, and copper. The inlet pollutant concentrations were used to calibrate SLAMM for industrial parking lots.

Results from the eight Wisconsin studies were combined to create an average concentration for each source area (Table 24. 2). Almost all of the average concentration values represent the results from more than one study. Because the constituent list was different for each study, the sample count varies considerably between the types of source areas. Sample counts are high for suspended solids and phosphorus, since they were analyzed during all the studies. Only one project (Marquette, MI) analyzed COD and PAHs for all the source areas, so these constituents have a low sample count. Censored values (samples having less than the detection limit) are included as one-half the detection limit for some of the constituents having low sample counts.

Although loads from a source area are greatly influenced by the volume of runoff, the large differences in some of the source area concentrations can decrease the importance of volume when comparing the loads from different source areas. For example, the volume of runoff from lawns is expected to be relatively low, but concentrations of phosphorus in lawn runoff are 2 to 10 times higher than for other source areas. Because of these relatively high concentrations, lawns can contribute as much as 50% of the annual total phosphorus load in a residential area (Washbusch, et al. 1999). With PAH levels from commercial parking lots 10 to 100 times higher than from any other source area, commercial parking lots representing only 3% of an urban drainage area can contribute 60% of the annual PAH load (Steuer, et al. 1997).

Concentrations for some of the pollutants can be compared between roofs and streets for all three land uses. Streets in industrial areas are likely important sources of suspended solids, total phosphorus, and zinc whenever they are compared to commercial and residential streets. But concentrations of these three pollutants in industrial roof runoff is similar to, or lower than, the other two land uses.

Enough data are compiled in Table 24.2 to determine pollutant loads from many of the typical urban source areas. However, more monitoring is needed to expand the list of constituents, especially in areas having low sample counts. Additional source areas also need to be monitored. Pesticides are an example of a pollutant not included in Table 24.2. Both lawns and undeveloped areas do not have any concentrations for PAHs. The sample count is very low for source areas having PAH, COD, and BOD data. Sample counts are less than five for 40 out of the 334 concentrations on the table. Gas stations are an example of a missing specific source area. Also missing are runoff concentrations from a range of parking lot types. Parking lots with high turnover are expected to experience higher pollutant concentrations than those

used for long-term employee parking, for example, and need to be better represented. *Table 24.2 (Wisconsin Source Area Monitoring Data) has been placed in the appendix at the end of this book.*

24.3 Other Source Area Stormwater Investigations

24.7.1 General Sources

Nowakowska-Blaszezyk, et al. (1996) studied the sources of wet-weather pollutants in Poland. It was found that storm runoff from parking areas and streets had the greatest concentrations of suspended solids (SS), chemical oxygen demand (COD), five-day biochemical oxygen demand (BOD₅), and Pb, while phosphorus was mostly contributed from landscaped-area storm runoff. Storm runoff from roofs covered with roofing paper was also a significant contributor of many pollutants.

Gromaire-Mertz, et al. (1999) collected stormwater runoff from 4 roofs, 3 courtyards and 6 streets on an experimental catchment in central Paris, France, and analyzed the samples for SS, VSS, COD, BOD₅, hydrocarbons, and heavy metals both in dissolved and particulate fractions. The street runoff showed large SS, COD and hydrocarbon loads, but the roof runoff had high concentrations of heavy metals.

Davis, et al. (2001) presented loading estimates of lead, copper, cadmium, and zinc in stormwater from different sources. They reviewed available data from the literature, and conducted controlled experiments and other sampling. Specific sources that they examined included building siding and roofs; automobile brakes, tires, and oil leakage; and wet and dry atmospheric deposition. The most important sources they identified were building siding for all four metals, vehicle brake emissions for copper, and tire wear for zinc. Atmospheric deposition was an important source for cadmium, copper, and lead.

24.3.2 Atmospheric Deposition Studies

Jordan, et al. (1997) estimated that 40% of the nitrogen (N) loading to the Chesapeake Bay watershed comes from atmospheric deposition, 33% from livestock waste, and 27% from fertilizer. Ahn and James (2001) reported that atmospheric deposition is a substantial source of phosphorus to the Florida Everglades. Phosphorus has been measured on a weekly basis since 1974, but

the results were highly variable: the average mean and standard deviation of the calculated P deposition rates for 13 sites were $41 \pm 33 \text{ mg P m}^{-2} \text{ yr}^{-1}$. They found that the atmospheric P deposition load showed high spatial and temporal variability, with no consistent long-term trend. Because of the random nature of P deposition, the estimated P deposition loads have a significant amount of uncertainty, no matter what type of collection instrument is used, and replicate sampling is highly recommended.

Atasi, et al. (1999 and 2001) conducted source monitoring using specialized sampling equipment and ultra-clean analytical methodology to quantify the concentrations and fluxes of mercury, cadmium, and polychlorinated biphenyl in ambient air, precipitation, runoff, sanitary sewer, and wastewater treatment plant influent. The relationships between the atmospheric deposition and runoff on controlled surfaces were also examined. Atmospheric deposition was found to be the primary source of these pollutants in runoff. They concluded that wet weather flows, not atmospheric deposition, contributed the main portion of these pollutants to the Detroit Wastewater Treatment Plant. Garnaud, et al. (1999) studied heavy metal concentrations in dry and wet atmospheric deposits in Paris, France, for comparison with urban runoff. Samples were continuously collected for 2 to 13 months at each of four test sites. Comparisons of median values of metal concentrations showed that rainwater contamination with heavy metals was only slightly higher in the center of Paris than at Fontainebleau (48 km SE of the city) which illustrates the medium range transport of atmospheric contamination. Glass and Sorensen (1999) examined a six-year trend (1990-1995) of wet mercury deposition in the Upper Midwest of the United States. The annual wet mercury deposition averaged $7.4 \text{ } \mu\text{g Hg/m}^2\text{-y}$ and showed significant variations between sites and illustrated significant increasing trends over the monitoring period. Warm (rain) season wet mercury deposition was found to average 77% of total annual wet deposition.

Tsai, et al. (2001) described their pilot study, conducted from August 1999 through August 2000, that estimated the loading of heavy metals from the atmosphere to San Francisco Bay. Dry deposition flux of copper, nickel, cadmium, and chromium was approximately 1100 ± 73 , 600 ± 35 , 22 ± 15 , and $1300 \pm 90 \text{ } \mu\text{g/m}^2\text{/y}$, respectively. The volume-weighted average concentrations of these trace metals in the rain water were 1.2, 0.4, 0.1, and $0.2 \text{ } \mu\text{g/L}$, respectively. Direct atmospheric deposition onto Bay waters, from both dry deposition and rainfall, contributed approximately 1900, 930, 93 and 1600 kg/y of copper, nickel, cadmium and chromium, respectively. Stormwater runoff contributed approximately twice as much as the loading

from direct atmospheric deposition. Direct atmospheric deposition was therefore found to be a minor contributor to the total load of these pollutants to the Bay. A mass balance of all known sources and sinks for heavy metals (Ag, Cd, Cu, and Pb) in New Haven Harbor, CT, was conducted by Rozan and Benoit (2001). Sources included direct atmospheric deposition, rivers, treated sewage effluent, combined sewer overflows, and permitted industrial discharges. All of the fluxes were directly measured, and the uncertainties were quantified. River inputs accounted for most of the total yearly metal discharges, while the salt marshes removed about 20 to 30% of the metals from the rivers before reaching the harbor. Atmospheric deposition is of minor importance, and is comparable to sewage effluent discharges. Schiff and Stolzenbach (2003) investigated the heavy metal contribution of atmospheric deposition to Santa Monica Bay and compared the atmospheric deposition loading to the loading from other sources. The annual atmospheric deposition of chromium, copper, lead, nickel and zinc exceeded the estimated annual effluent loads from industrial and power generating stations to Santa Monica Bay.

24.3.3 Roof Runoff and Other Building Materials

Sakakibara (1996) investigated roof runoff quality in Ibaraki prefecture, Japan, in order to determine the feasibility of using roof runoff in urban areas for various beneficial uses. Eighty three samples were collected during one year and analyzed for pH (averaged 6.1), BOD₅ (averaged 1.6 mg/L), COD (averaged 3.2 mg/L), and SS (averaged 12 mg/L). It was concluded that roof runoff could be used for toilet flushing and landscaping watering with minimal treatment or problems.

Heavy metals and major ions in roof-runoff were investigated by Förster (1996) in Bayreuth, Germany. It was found that the major ions were from the rain, while very high Cu and Zn concentrations were from metal flashings used on the roofs. It was concluded that the best option would be to abandon the use of exposed metal surfaces on roofs and walls of buildings. Pesticides present in rainwater do not pose a greater groundwater contamination problem during artificial roof runoff infiltration (a practice in Switzerland to reduce runoff) than does the direct application in agriculture (Bucheli, et al. 1998a); however, the herbicide (R,S)-mecoprop, a root protection agent in Preventol B 2 commonly applied to roofs, is of the same order of magnitude as loads from agricultural applications (Bucheli, et al. 1998b). Förster (1999) and Förster, et al. (1999) summarized their studies investigating roof runoff as a stormwater

pollutant source. Runoff samples were taken from an experimental roof system containing five different roofing materials and from house roofs at five different locations in Bayreuth, Germany. It was found that local sources (e.g. PAH from heating systems), dissolution of the roof systems' metal components, and background air pollution were the main sources of the roof runoff pollution. They found that the first flush from the roofs often was heavily polluted and should be specially treated. They concluded that roofs having metal surfaces should not be connected to infiltration facilities as concentrations of copper and zinc far exceed various toxicity threshold values. They also examined a green (vegetated) roof for comparison. These roofs were found to act as a source of heavy metals which were found to be in complexes with dissolved organic material. Leaching from unprotected zinc sheet surfaces on the green roofs resulted in extremely high zinc concentrations in the runoff. In contrast, the green roofs were a trap for PAHs.

Davis and Burns (1999) examined lead concentrations in runoff from painted surfaces. In many tests, high lead concentrations were found (using 100 mL of wash water over 1600 cm² of surface). Lead concentrations from 169 different structures followed the following order (median concentrations in the wash water): wood (49 µg/L) > brick (16 µg/L) > block (8.0 µg/L). Lead concentration depended strongly on paint age and condition, with the lead levels from washes of older paints being much higher than from freshly painted surfaces. Lead from surface washes were found to be 70%, or greater, in particulate lead form, suggesting the release of lead pigments from the weathered paints.

Zobrist, et al. (2000) examined the potential effects of roof runoff on urban stormwater drainage from three different types of roofs: an inclined tile roof, an inclined polyester roof and a flat gravel roof. Runoff from the two inclined roofs showed initially high ("first flush") concentrations of the pollutants with a rapid decline to lower levels. The flat gravel roof showed lower concentrations of most of the pollutants because of the ponding of the water on the roof surface acting like a detention pond. Pollutant loadings were similar to atmospheric deposition, with the exception of copper from drain corrosion (rate about 5 g/m²/y). Tobiasson and Logan (2000) used the whole effluent toxicity (WET) test to characterize stormwater runoff samples from four outfalls at Sea-Tac International Airport. Three of the four outfalls met standards; the source of the toxicity at the fourth outfall was found to be zinc-galvanized metal rooftops. Typically, more than 50% of the total zinc in the runoff was in dissolved form and likely bioavailable. Polkowska, et al. (2002) presented the results of testing roof runoff waters from buildings in Gdansk, Poland. More than half of the samples (25) were found to be toxic, with

inhibition exceeding 20%. The toxicity was weakly correlated to the levels of organonitrogen and organophosphorus pesticides in runoff waters. It was established that at least in some cases the roofing material affected the levels of the pollutants found in the samples. Heijerick, et al. (2002) investigated the bioavailability of zinc in runoff from roofing materials in Stockholm, Sweden. Chemical speciation modeling revealed that most zinc (94.3-99.9%) was present as the free Zn ion, the most bioavailable speciation form. These findings were confirmed by the results of the biosensor test (BiometTM), which indicated that all zinc was indeed bioavailable. Analysis of the ecotoxicity data also suggested that the observed toxic effects were due to the presence of Zn²⁺ ions. Gromaire, et al. (2002) investigated the impact of zinc roofing on urban pollutant loads in Paris. On an annual basis, runoff from Parisian zinc roofs would produce around 34 to 64 metric tons of zinc and 15 to 25 kg of cadmium, which is approximately half the load generated by runoff from all of Paris.

Karlen, et al. (2002) investigated runoff rates, chemical speciation and bioavailability of copper released from naturally patinated copper roofs in Stockholm, Sweden. The results show annual runoff rates between 1.0 and 1.5 g/m² year for naturally patinated copper of varying age with rates increasing slightly with patina age. The total copper concentration in investigated runoff samplings ranged from 0.9 to 9.7 mg/L. The majority (60 – 100%) of the released copper was present as the free hydrated cupric ion, Cu(H₂O)₆²⁺, the most bioavailable copper species. The copper-containing runoff water, sampled directly after release from the roof, caused significant reduction in growth rate of the green alga. Wallinder, et al. (2002) studied the atmospheric corrosion of naturally and pre-patinated copper roofs in Singapore and Stockholm. Measured annual runoff rates from fresh and brown prepatinated were 1.1-1.6 g/m² and 5.5-5.7 g/m², in Stockholm and Singapore, respectively. Naturally aged copper sheet (130 years old) and green pre-patinated copper sheet showed slightly higher (1.6-2.3 g/m²), but comparable runoff rates in Stockholm. In Singapore, runoff rates from green pre-patinated copper sheet were 8.4-8.8 g/m². Comparable runoff rates between fresh and brown-patinated copper sheet and between green naturally patinated and green pre-patinated copper sheet at each site were related to similarities in patina morphology and composition. Boller and Steiner (2002) investigated the emission and control of copper from roofs and roads in urban surface runoff. A large copper façade was used to investigate the concentrations of copper emitted. The concentrations ranged from 1 – 10 mg/L. Michels, et al. (2003) investigated the environmental impact of stormwater runoff from a

copper roof. It was shown that the runoff became less toxic as it passed through the drainage system.

Clark, et al. (2003) studied the potential pollutant contributions from commonly-used building materials (roofing, siding, wood) using a modified Toxicity Characteristic Leaching Procedure (TCLP) test. Results of particular interest included evidence of elevated levels of phosphate, nitrate and ammonia in the leachant following exposure of common roofing and siding materials to simulated acid rain.

Lebow, et al. (2003) investigated the release of preservatives, primarily arsenic, from CCA-treated wood under simulated rainfall and the ability of wood finishes to prevent/reduce the release. Water repellent significantly decreased the amounts of these elements in the runoff, while UV exposure increased the leaching of preservatives from the wood.

24.3.4 Highway and other Roadway Runoff

Wada and Miura (1996) examined storm runoff from a heavily traveled highway in Osaka, Japan. A significant “first-flush” for COD was found and the amount of small rubber pieces from tire wear in the highway storm runoff was more than 20 times greater than for an “ordinary” road. The primary factors affecting storm runoff concentrations were the amount of traffic (and related exhaust emissions and tire wear) and the fraction of the total traffic that was comprised of trucks and buses. Montrejaud-Vignoles, et al. (1996) collected storm runoff from a heavily used six-lane motorway in the Mediterranean area of France. The very irregular rainfall in this area and associated very-long dry periods can result in storm runoff that is much more polluted than elsewhere in France. As an example, during the one-year study, a single rain of only 10 mm but having an antecedent-dry period of 35 days produced more than 12% of the annual COD discharges. Ball, et al. (1996) and Ball 2000 examined roadway pollutant accumulations in a suburb of Sydney, Australia. It was concluded that the local heavy winds have a significant effect on pollutant accumulations that commonly available stormwater models do not consider, and that historical United States’ data on roadway-pollutant accumulations are much greater than found in their area.

Sansalone and Buchberger (1996) studied metal distributions in stormwater and snowmelt from a major highway in Cincinnati, OH. Zn and Cd were mostly in filterable (dissolved solids) forms in the storm runoff, while lead was mostly associated with particulates. A receptor-source model was used to apportion source contributions for PAH in street and creek

sediments. The model showed that vehicles along with the coke ovens, are the major contributors to PAH in street sediments (Sharma et al., 1997). Measurements of conductivity and turbidity taken in a study of the Crum Creek which runs through the suburbs of Philadelphia, Pa. indicated two stages during the first three hours of wet weather runoff: a dissolved solids flush followed by a suspended solids (SS) flush (Downing and McGarity 1998). In San Francisco, Calif., vehicle emissions of both ultrafine ($< 0.12 \mu\text{m}$) and accumulation mode ($0.12 - 2 \mu\text{m}$) particulate polycyclic aromatic hydrocarbons (PAH) are derived from diesel vehicles while gasoline vehicles emit higher molecular weight PAH primarily in the ultrafine mode. Heavy duty diesel vehicles were found to be important sources of fine black carbon particles (Miguel, et al. 1998). In a European study, 90% of the particles from a contaminated highway runoff catchment were smaller than $100 \mu\text{m}$. The constituents of the contaminants smaller than $50 \mu\text{m}$ were further analyzed by X-ray diffraction, thermogravimetry and specific mass and contained 56% clay, 15% quartz, 12% chalk, 9% organic matter, 5% feldspars, and 2% dolomite (Roger, et al. 1998).

Waschbusch, et al. (1999) investigated sources of phosphorus in stormwater and street dirt from two urban residential basins in Madison, Wisconsin. They collected numerous sheetflow runoff samples from throughout the test watersheds and used SLAMM, an urban stormwater quality model, to quantify the significance of the different phosphorus sources. Lawns and streets were found to be the most significant sources of phosphorus in the test basins, contributing about 80% of the total annual loading. In the Kerault Region of France, the effects of pollution were studied using solid matter from a section of the A9 motorway. This study analyzed both settled sediments from collecting basin and characteristics of sediments in the water column during and after eight storm events between October 12, 1993, and February 6, 1994. Settled sediments were used to measure particle sizes, mineral content, and related characteristics, whereas water samples were used to document total suspended solids, mineral content, and heavy metals (Andral, et al. 1999). Runoff from highways contains significant loads of heavy metals and hydrocarbons, according to German regulations it should be infiltrated over embankments to support groundwater recharge. To investigate the decontaminating effect of greened embankments, soil-monoliths from highways with high traffic densities were taken. Soils were analyzed to characterize the contamination in relation to distance and depth for lead, zinc, copper, cadmium, PAH and MOTH (Dierkes and Geiger 1999).

An investigation by Drapper, et al. (2000) showed that the pollutant concentrations (heavy metals, hydrocarbons, pesticides, and physical characteristics) in 'first flush' road runoff in Brisbane in southeast Queensland, Australia was within the ranges reported internationally for highways. Traffic volumes were the best indicator of road runoff pollutant concentrations, with interevent duration also being statistically significant factor. Exit-lane sites were found to have higher concentrations of acid-extractable copper and zinc, likely due to brake pad and tire wear caused by rapid deceleration, and laser particle sizing showed that a significant proportion of the sediment in runoff was less than 100 μm . Krein and Schorer (2000) investigated heavy metals and PAHs in road runoff and found that, as expected, an inverse relationship existed between particle size and particle-bound heavy metals concentration existed. However, particulate bound PAHs were found to be bimodally distributed. Three-ring PAHs were mostly found in the fine sand fraction, while six-ring PAHs were mostly concentrated in the fine silt fraction. Sutherland, et al. (2000) investigated the potential for road-deposited sediments in Oahu, Hawaii, to bind contaminants, and thus transporting these bound contaminants to the receiving water as part of the runoff. In the sediment fractions less than 2 mm in diameter, the origins of the aluminum, cobalt, iron, manganese and nickel were determined to be geologic. Three of the metals concentrations, copper, lead and zinc, were found to be enhanced by anthropogenic activities. Sequential extraction of the sediment determined the associations of the metals with the following fractions: acid extractable, reducible, oxidizable, and residual).

Stenstrom, et al. (2001) studied freeway runoff from three sites in the west Los Angeles area. Each site was sampled for 14 storms during the 1999-2000 rain season. Samples were collected very early in the storm in order to compare water quality from the first runoff to water quality from the middle of the storm. A large range of water quality parameters and metals were analyzed. The data showed large first flushes in concentration and moderate first flushes in mass emission rates. Neary, et al. (2002) studied the pollutant washoff and loadings from parking lots in Cookeville, Tennessee. The monitoring results indicated that the washoff response from small parking lot catchments was also affected by other factors that included antecedent dry conditions and rainfall intensity. Ma, et al. (2002) investigated the first-flush phenomenon for highways. Most pollutants showed median mass first flushes where 30% of the mass is released in the first 20% of the runoff. Pollutants representing organic contaminants had the highest first flush ratios. Lau, et al. (2002) studied whether a first flush of organics (COD, oil and grease, and PAHs) would be seen in highway runoff. The three highway sites exhibited a

first flush in most cases for most parameters. The mass first flush ratio (the ratio of the normalized transported mass of pollutant to the normalized runoff volume) generally was above 1.8 for the first 25% of the runoff volume, and in some cases as high as 2.8.

Vaze and Chiew (2003) studied pollutant washoff from small impervious experimental plots and showed that the energy of the falling raindrops was important at the beginning of the event where the concentration/prevalence of easily detachable pollutants is greatest. The authors suggest that meaningful characteristic curves that relate event total suspended solids (TSS) and total phosphorus (TP) loads to storm durations for specific rainfall intensities could be developed from the experimental data. Kayhanian, et al. (2003) investigated the relationships between annual average daily traffic (AADT) numbers and highway runoff pollutant concentrations from California Department of Transportation highway sites. No direct linear correlation was found between highway runoff pollutant event mean concentrations (EMCs) and AADT, but multiple linear regression showed that AADT, as well as antecedent dry period (ADP), drainage area, maximum rain intensity and land use, influenced most highway runoff constituent concentrations. Mishra, et al. (2003) developed hysteresis and normal mass rating curves were developed for runoff rate and mass of 12 dissolved and particulate bound metal elements from Cincinnati, OH. Zinc was found to increase with antecedent dry period (ADP). Shinya, et al. (2003) evaluated the factors influencing diffusion of highway pollutant loads in urban highway runoff. Particulates (suspended solids, iron and TP) were inclined to be washed off in heavier rainfall; event mean runoff intensity and cumulative runoff height were correlated with cumulative runoff load of the constituents except TN. ADP and traffic flow volume were not correlated with cumulative runoff load (except TN). Sutherland (2003) investigated the lead in six grain-size fractions of road-deposited sediment from Oahu, HI. Significant Pb concentration was seen in all samples and the median labile Pb concentration was 170 mg/kg (4 to 1750 mg/kg), with the silt plus clay fraction containing 38% of the total sediment in this fraction.

Landscaped Areas

Emerson (2003) discussed Plymouth, MN restrictions on the use of lawn fertilizers containing phosphorus. The result of the program has been an improvement in water quality due to reducing phosphorus in the runoff. Strynchuk, et al. (2003) studied the decomposition of grass and leaves and the subsequent input of nutrients to receiving waters in Brevard County, FL.

Release rates for these nutrients have been calculated, which can then be used to select and determine maintenance frequencies of stormwater control practices that treat nutrients.

24.4 Conclusions

The greatest detection frequencies for organic toxicants were for 1,3-dichlorobenzene and fluoranthene, which were each detected in 23% of the Birmingham area samples. The organics most frequently found in these source area samples (i.e., fluoranthene and pyrene) were similar to the organics most frequently detected at outfalls in prior studies. In contrast to the organics, the heavy metals analyzed were detected in almost all samples, including the filtered sample portions.

The volume of runoff from Wisconsin lawns is expected to be relatively low, but concentrations of phosphorus in lawn runoff are 2 to 10 times higher than for other source areas. Because of these relatively high concentrations, lawns can contribute as much as 50 % of the annual total phosphorus load in a residential area. Similarly, with PAH levels from commercial parking lots 10 to 100 times higher than from any other source area, commercial parking lots representing only 3% of an urban drainage area can contribute 60% of the annual PAH load

References

- Ahn, G., and James, R.T. Variability, Uncertainty, and Sensitivity of Phosphorus Deposition Load Estimates in South Florida. *Water Air Soil Poll.* 126:37. 2001
- Andral, M.C.; Roger, S.; Montrejaud-Vignoles, M.; and Herremans, L. Particle Size Distribution and Hydrodynamic Characteristics of Solid Matter Carried by Runoff from Motorways, *Water Environ. Res.*, 71, 4, 398. 1999
- Atasi, K.Z.; Fugita, G.; LePlatte, G.; Hufnagel, C.; Keeler, G.; Graney, J.; and Chen, T. Impact of Atmospheric Deposition on the Headworks of Wastewater Treatment Plant – A Case Study. *Proc. Water Environ. Fed. 72nd Annu. Conf. Exposition*, [CD-ROM], New Orleans, LA. 1999
- Atasi, K.; Fujita, G.; and LePlatte, G. Study: air deposition contributes significantly to toxic chemical load in runoff. *Watershed & Wet Weather Technical Bulletin*. July, 2001
- Ball, J.E., Jenks, R., and Auborg, D. Dry Weather Build-up of Constituents on Road Surfaces. *Proc. 7th Int. Conf. on Urban Storm Drainage*, Hannover, Germany, IAHR/IAWQ Joint Committee on Urban Storm Drainage, 785. 1996

- Ball, J.E. Runoff from Road Surfaces - How Contaminated is It? Proc. Hydro 2000 - Hydrology and Water Resources Symposium, Perth, WA, Australia. 2000
- Bannerman, R., K. M. Baun, P. E. Bohn, and D. A. Graczyk. Evaluation of Urban Nonpoint Source Pollution Management in Milwaukee County, Wisconsin. PB 84-114164. U.S. Environmental Protection Agency. Chicago, IL. 1983
- Boller, M.A.; Steiner, M. Diffuse emission and control of copper in urban surface runoff. *Water Science and Technology*, 46(6-7), 173-181. 2002
- Bucheli, T.; M. Iler, S.; Herberle, S.; and Schwarzenbach, R. Occurance and Behavior of Pesticides in Rainwater, Roof Runoff and Artificial Stormwater Infiltration. *Environ. Sci. Technol.*, 32, 22, 3457. 1998a
- Bucheli, T.; M. Iler, S.; Voegelin, A; and Schwarzenbach, R. Bituminous Roof Sealing Membranes as Major Sources of the Herbicide (R,S)-Mecoprop in Roof Runoff Waters: Potential Contamination of Groundwater and Surface Waters. *Environ. Sci. Technol.*, 32, 22, 3465. 1998b
- Burton, G.A. Jr., and R. Pitt. Stormwater Effects Handbook: A Tool Box for Watershed Managers, Scientists, and Engineers. CRC Press, Inc., Boca Raton, FL. 2002. 911 pages.
- Clark, S.E.; Lalor, M.M.; Pitt, R.; Field, R. Contribution of commonly-used building materials to wet weather pollution. WEFTEC 2003 Conf. Proc. Water Environment Federation. CD-ROM. 2003
- Corsi, S.R., Greb, S.R., Bannerman, R.T., and Pitt, R.E. Evaluation of the multi-chambered treatment train, a retrofit water-quality management device, U.S. Geological Survey Open-File Report 99-270, 24p. 1999
- Davis, A.P., and Burns, M. Evaluation of Lead Concentration in Runoff from Painted Structures. *Water Res. (G.B.)*, 33, 13, 2949. 1999
- Davis, A.P.; Shokouhian, M.; and Ni, S.B. Loading Estimates of Lead, Copper, Cadmium, and Zinc in Urban Runoff from Specific Sources. *Chemosphere*. 44:997. 2001
- Dierkes, C., and Geiger, W.F. Pollution Retention Capabilities of Roadside Soils. *Water Sci. Technol. (G.B.)*, 39, 2, 201. 1999
- Downing, S. L. and McGarity, A. E. Wet Weather Pollution Effects on Water Quality in Crum Creek. Proc. Adv. in Urban Wet Weather Pollut. Reduction, Cleveland, Ohio, WEF (CP3805), 473. 1998
- Drapper, D.; Tomlinson, R.; and Williams, P. Pollutant Concentrations in Road Runoff: Southeast Queensland Case Study. *J. Environ. Eng.* 126, 313. 2000
- Emerson, D. Restricting phosphorus key to surface water management. *BioCycle*. 44(2):48-52. 2003
- EPA. Methods for Organic Chemical Analyses of Municipal and Industrial Wastewater. Environmental Monitoring and Data Support Laboratory. EPA-600/4-82-057. U.S. Environmental Protection Agency. Cincinnati, OH. 1982
- EPA. Results of the Nationwide Urban Runoff Program. Water Planning Division. PB 84-185552. Washington, D.C. December. 1983a
- EPA. Methods for Chemical Analysis of Water and Wastes. EPA-600/4-79-020. U.S. Environmental Protection Agency. Cincinnati, OH. 1983b
- Förster, J. Heavy Metal and Ion Pollution Patterns in Roof Runoff. Proc. 7th Int. Conf. on Urban Storm Drainage, Hannover, Germany, IAHR/IAWQ Joint Committee on Urban Storm Drainage, 241. 1996

- Förster, J. Variability of Roof Runoff Quality. *Water Sci. and Tech.* 39, 5, 137. 1999
- Förster, J. and Knoche, G. Quality of Roof Runoff From Green Roofs. *Proc. the Eighth International Conference on Urban Storm Drainage*. August 30 – September 3, 1999, Sydney, Australia. Edited by IB Joliffe and JE Ball. The Institution of Engineers Australia, The International Association for Hydraulic Research, and The International Association on Water Quality, 1312. 1999
- Garnaud, S.; Mouchel, J-M.; and Thevenot, D.R. Mobility Evolution of Particulate Trace Metals in Urban Runoff: From Street Deposits and Road Runoff to Combined Sewer Deposits and Catchment Outlet. *Proc. the Eighth International Conference on Urban Storm Drainage*. August 30 – September 3, 1999, Sydney, Australia. Edited by IB Joliffe and JE Ball. The Institution of Engineers Australia, The International Association for Hydraulic Research, and The International Association on Water Quality, 1511. 1999
- Glass, G.E., and Sorensen, J.A. Six-year trend (1990-1995) of Wet Mercury Deposition in the Upper Midwest USA. *Environ. Sci. Technol.* 33, 19, 3303. 1999
- Gromaire-Mertz, M.; Chebbo, G.; and Saad, M. Origins and Characteristics of Urban Wet Weather Pollution in Combined Sewer Systems-The Experimental Urban Catchment "Le Marais" in Paris. *Proc. 2nd Int. Conf. The Sewer as a Physical, Chemical and Biological Reactor*, Aalborg, Den. 1997
- Gromaire, M.C.; Chebbo, G.; Constant, A. Impact of zinc roofing on urban runoff pollutant loads: The case of Paris. *Water Science and Technology*, 45(7), 113-122. 2002
- Heijerick, D.G.; Janssen, C.R.; Karlen, C.; Odnevall Wallinder, I. Leygraf, C. Bioavailability of zinc in runoff water from roofing materials. *Chemosphere*, 47(10), 1073-1080. 2002
- Holmstrom, B.K., and others, Water resources data, Wisconsin, water year 1995: U.S. Geological Survey Water –Data Report WI-95, pp33. 1995
- Holmstrom, B.K., and others, Water resources data, Wisconsin, water year 1996: U.S. Geological Survey Water –Data Report WI-95, pp.35. 1996
- Jordan, T. E., Correl, D. L. and Weller, D. E. Nonpoint Source Discharges of Nutrients from Piedmont Watersheds of Chesapeake Bay. *J. Am. Water Resour. Assoc.*, 33, 3, 631. 1997
- Karlen, C.; Odnevall Wallinder, I.; Heijerick, D.; Leygraf, C. Runoff rates, chemical speciation and bioavailability of copper released from naturally patinated copper. *Environmental Pollution*, 120(3), 691-700. 2002
- Kayhanian, M.; Singh, A.; Suverkrupp, C.; Borroum, S. Impact of annual average daily traffic on highway runoff pollutant concentrations. *J. Environ. Eng.* 129(11):975-990. 2003
- Krein, A., and Schorer, M. Road Runoff Pollution by Polycyclic Aromatic Hydrocarbons and its Contribution to River Sediments. *Water Res. (G.B.)*. 34, 4110. 2000
- Lau, S.-L.; Ma, J.-S.; Kayhanian, M.; Stenstrom, M.K. First flush of organics in highway runoff. *Global Solutions for Urban Drainage*, *Proc. of the Ninth Int. Conf. on Urban Drainage*, Sept 8-13 2002, Portland, OR, CD-ROM. 2002
- Lebow, S.; Williams, R.S.; Lebow, P. Effects of simulated rainfall and weathering on release of preservative elements from CCA treated wood. *Environ. Sci. Technol.* 37(18):4077-4082. 2003

- Ma, J.-S.; Khan, S.; Li, Y.-X.; Kim, L.-H.; Ha, S.; Lau, S.-L.; Kayhanian, M.; Stenstrom, M.K. First flush phenomena for highways: How it can be meaningfully defined. *Global Solutions for Urban Drainage, Proc. of the Ninth Int. Conf. on Urban Drainage*, Sept 8-13 2002, Portland, OR, CD-ROM. 2002
- Michels, H.T.; Boulanger, B.; Nikolaidis, N.P. Environmental impact of stormwater runoff from a copper roof. *Mater. Perform.* 42(2):70-74. 2003
- Miguel, A.H.; Kerchstetter, T.W.; and Harley, R.A. On-Road Emissions of Particulate Polycyclic Aromatic Hydrocarbons and Black Carbon from Gasoline and Diesel Vehicles. *Environ. Sci. Technol.* 32, 4, 450. 1998
- Mishra, S.K.; Sansalone, J.J.; Singh, V.P. Hysteresis-based analysis of overland metal transport. *Hydrol. Process.* 17(8):1579-1606. 2003
- Montrejaud-Vignoles, M., Roger, S., and Herremans, L. Runoff water pollution of motorway pavement in Mediterranean area. *Proc. 7th Int. Conf. on Urban Storm Drainage*, Hannover, Germany, IAHR/IAWQ Joint Committee on Urban Storm Drainage, 247. 1996
- Neary, V.S.; Neel, T.C.; Dewey, J.B. Pollutant washoff and loading from parking lots in Cookeville, Tennessee. *Global Solutions for Urban Drainage, Proc. of the Ninth Int. Conf. on Urban Drainage*, Sept 8-13 2002, Portland, OR, CD-ROM. 2002
- Nowakowska-Blaszczyk, A., and Zakrzewski, J. The Sources and Phases of Increase of Pollution in Runoff Waters in Route to Receiving Waters. *Proc. 7th Int. Conf. on Urban Storm Drainage*, Hannover, Germany, IAHR/IAWQ Joint Committee on Urban Storm Drainage, 49. 1996
- Pitt, R. and J. McLean. Toronto Area Watershed Management Strategy Study. Humber River Pilot Watershed Project. Ontario Ministry of the Environment. Toronto, Ontario. 1986
- Pitt, R. and J. Voorhees. "Source loading and management model (SLAMM)." Seminar Publication: National Conference on Urban Runoff Management: Enhancing Urban Watershed Management at the Local, County, and State Levels. March 30 – April 2, 1993. Center for Environmental Research Information, U.S. Environmental Protection Agency. EPA/625/R-95/003. Cincinnati, Ohio. pp. 225-243. April 1995.
- Pitt, R., R. Field, M. Lalor, and M. Brown. Urban stormwater toxic pollutants: assessment, sources and treatability., *Water Environment Research*. Vol. 67, No. 3, pp. 260-275. May/June 1995. Discussion and closure in Vol. 68, No. 4, pp. 953-955. July/August 1996.
- Polkowska, Z.; Gorecki, T.; Namiesnik, J. Quality of roof runoff waters from an urban region (Gdansk, Poland). *Chemosphere*, 49(10), 1275-1283. 2002
- Roa-Espinaosa, A., and R.T. Bannerman. Monitoring BMP effectiveness at industrial sites. pp 467-486, In *Stormwater NPDES Related Monitoring Needs, Proceedings of an Engineering Foundation Conference* ed. By H.C.Torno. Mount Crested Butte, CO., American Society of Civil Engineers, New York, NY. 1994.
- Roger, S.; Montrejaud-Vignoles, M.; Adral, M. C.; Herremans, L.; and Fortune, J. P. Mineral, Physical and Chemical Analysis of the Solid Matter carried by Motorway Runoff Water. *Water Res. (GB)*, 32, 4, 1119. 1998
- Rozan, T.F., and Benoit, G. Mass Balance of Heavy Metals in New Haven Harbor, Connecticut: Predominance of Nonpoint Sources. *Limnology Oceanography*. 46:2032. 2001

- Sakakibara, T. Roof Runoff Storm Water Quality. Proc. 7th Int. Conf. on Urban Storm Drainage, Hannover, Germany, IAHR/IAWQ Joint Committee on Urban Storm Drainage, 157. 1996
- Sansalone, J.J., and Buchberger, S.G. Characterization of Solid and Metal Element Distributions in Urban Highway Stormwater. Proc. 7th Int. Conf. on Urban Storm Drainage, Hannover, Germany, IAHR/IAWQ Joint Committee on Urban Storm Drainage, 253. 1996
- Schiff, K.; Stolzenbach, K. Contribution of trace metals via atmospheric deposition to Santa Monica Bay and the Santa Monica Bay watershed. TMDL 2003 Conf. Proc. Water Environment Federation. CD-ROM. 2003
- Sharma, M.; Mcbean, E. A.; and Marsalek, J. Source Characterization of Polycyclic Aromatic Hydrocarbons in Street and Creek Sediments. Water Qual. Res. J. Canada, 32, 1, 23. 1997
- Shinya, M.; Tsuruho, K.; Konishi, T.; Ishikawa, M. Evaluation of factors influencing diffusion of pollutant loads in urban highway runoff. Water Sci. Technol. 47(7-8):227-232. 2003
- Stenstrom, M.K.; Lau, S.-L.; Lee, H.-H.; Ma, J.-S.; Ha, H.; Kim, L.-H.; Khan, S.; and Kayhanian, M. First Flush Stormwater Runoff from Highways. Proc. ASCE EWRI Conf. - Bridging the Gap: Meeting the World's Water and Environmental Resources Challenges. CD-ROM. 2001
- Steuer, Jeffrey, William Selbig, Nancy Hornewer, and Jeffrey Prey, Sources of Contamination in an Urban Basin in Marquette, Michigan and an Analysis of Concentrations, Loads, and Data Quality, U.S. Geological Survey Water-Resources Investigations Report 97-4242. Middleton, Wisconsin, 1997
- Strynchuk, J., J.C. Royal and G.B. England. 2003. "Study of Decomposition of Grass and Leaves." *Journal of Water Management Modeling* R215-19. doi: 10.14796/JWMM.R215-19.
- Sutherland, R.A.; Tack, F.M.G.; Tolosa, C.A.; and Verloo, M.G. Operationally Defined Metal Fractions in Road Deposited Sediment, Honolulu, Hawaii. J. Environ. Qual. 29, 1431. 2000
- Sutherland, R.A. Lead in grain size fractions of road-deposited sediment. Environ. Pollut. 121(2):229-237. 2003
- Tobiason, S.A., and Logan, L.R.J. Stormwater Whole Effluent Toxicity (WET) Testing and Source Tracing at Sea-Tac International Airport. WEFTEC2000, 73rd Annual Conference and Exposition, October 2000, Anaheim, CA. Water Environment Federation, CD-ROM. 2000
- Tsai, P.; Hansen, E.; and Lee, K. Atmospheric Deposition of Trace Metals in San Francisco Bay Area. WEFTEC 2001 Conf. Proc. CD-ROM. 2001
- Vaze, J.; Chiew, F.H.S. Study of pollutant washoff from small impervious experimental plots. Water Resour. Res. 39(6):[np]. 2003
- Wada, Y., Miura, H., and Muraoka, O. Influence of Discharge Pollutants from the Highway at Rainfall on Water Quality of the Public Water Body. Proc. 7th Int. Conf. on Urban Storm Drainage, Hannover, Germany, IAHR/IAWQ Joint Committee on Urban Storm Drainage, 461. 1996

- Wallinder, I.O., and Leygraf, C. Seasonal Variations in Corrosion Rate and Runoff Rate of Copper Roofs in an Urban and a Rural Atmospheric Environment. *Corrosion Sci.* 43:2379. 2001
- Wallinder, I.O.; Korpinen, T.; Sundberg, R.; Leygraf, C. Atmospheric corrosion of naturally and pre-patinated copper roofs in Singapore and Stockholm - Runoff rates and corrosion product formation. ASTM Special Technical Publication: Outdoor Atmospheric Corrosion, 1421, 230-244. 2002
- Waschbusch R.J., Evaluation of the effectiveness of an urban stormwater treatment unit in Madison, Wisconsin, 1996-9, Water –Resources Investigations Report 99-4195, 49 p, 1999.
- Waschbusch, R.J., Bannerman, R.T., and Greb, S. R., in press, Yields of Selected Constituents in Street Runoff in Madison, Wisconsin, 1994-95: U.S. Geological Survey Water-Resources Investigation Report – in press
- Zobrist, J.; Muller, S.R.; Ammann, A.; Bucheli, T.D.; Mottier, V.; Ochs, M.; Schoenenberger, R.; Eugster, J.; and Boller, M. Quality of Roof Runoff for Groundwater Infiltration. *Water Res. (G.B.)*. 34:1455. 2000

APPENDIX A: Sources of Pollutants in Urban Areas.

Robert Pitt, Roger Bannerman, Shirley Clark and Derek Williamson

Oversize tables from Chapters 23 and 24.

Oversize table from Chapter 23.

Table 23.7

Pollutant and Land Use	Roofs	Paved Parking	Paved Storage	Unpaved Parking/Storage	Paved Driveways	Unpaved Driveways	Dirt Walks	Paved Sidewalks	Streets
<u>Total Solids (mg/L)</u>									
Residential:	58 (5) 64 (1) 18 (4)	1790 (5)	73 (5)		510 (5)		1240 (5)	49 (5)	325 (5) 235 (4)
Commercial:	95 (1) 190 (4)	340 (2) 240 (1) 102 (7)							325 (4)
Industrial:	113 (5)	490 (5)	270 (5)	1250 (5)	506 (5)	5620 (5)		580 (5)	1800 (5)
<u>Suspended Solids (mg/L)</u>									
Residential:	22 (1) 13 (5)	1660 (5)	41 (5)		440 (5)		810 (5)	20 (5)	242 (5)
Commercial:		270 (2) 65 (1) 41 (7)							242 (5)
Industrial:	4 (5)	306 (5)	202 (5)	730 (5)	373 (5)	4670 (5)		434 (5)	1300 (5)

Pollutant and Land Use	Roofs	Paved Parking	Paved Storage	Unpaved Parking/Storage	Paved Driveways	Unpaved Driveways	Dirt Walks	Paved Sidewalks	Streets
<u>Dissolved Solids (mg/L)</u>									
Residential:	42 (10 5 (5))	130 (5)	32 (5)		70 (5)		430 (5)	29 (5)	83 (5) 83 (4)
Commercial:		70 (2) 175 (1) 61 (7)							83 (5)
Industrial:	109 (5)	184 (5)	68 (5)	520 (5)	133 (5)	950 (5)		146 (5)	500 (5)
<u>BOD₅ (mg/L)</u>									
Residential:	3 (4)	22 (4)							13 (4)
Commercial:	7 (4)	11 (1) 4 (8)							

Pollutant and Land Use	Roofs	Paved Parking	Paved Storage	Unpaved Parking/Storage	Paved Driveways	Unpaved Driveways	Dirt Walks	Paved Sidewalks	Streets
<u>Total Phosphorus (mg/L)</u>									
Residential:	0.03 (5) 0.05 (1) 0.1 (4)				0.36 (5)		0.20 (5)	0.80 (5)	0.62 (5) 0.31 (4)
Commercial:	0.03 (4) 0.07 (4)	0.16 (1) 0.15 (7) 0.73 (5) 0.9 (2) 0.5 (4)							0.62 (5)
Industrial:	<0.06 (5)	2.3 (5)	0.7 (5)	1.0 (5)	0.9 (5)	3.0 (5)		0.82 (5)	1.6 (5)
<u>Total Phosphate (mg/L)</u>									
Residential:	<0.04 (5) 0.08 (4)				<0.2 (5)		0.66 (5)	0.64 (5)	0.07 (5) 0.12 (4)
Commercial:	0.02 (4)	0.03 (5) 0.3 (2) 0.5 (4) 0.04 (7) 0.22 (8)	<0.02 (5)						0.07 (5)
Industrial:	<0.02 (5)	0.6 (5)	0.06 (5)	0.13 (5)	<0.02 (5)	0.10 (5)		0.03 (5)	0.15 (5)

Pollutant and Land Use	Roofs	Paved Parking	Paved Storage	Unpaved Parking/Storage	Paved Driveways	Unpaved Driveways	Dirt Walks	Paved Sidewalks	Streets
<u>TKN (mg/L)</u>									
Residential:	1.1 (5) 0.71 (4)				3.1 (5)		1.3 (5)	1.1 (5)	2.4 (5) 2.4 (4)
Commercial:	4.4 (4)	3.8 (5) 4.1 (2) 1.5 (4) 1.0 (1) 0.8 (8)							2.4 (5)
Industrial:	1.7 (5)	2.9 (5)	3.5 (5)	2.7 (5)	5.7 (5)	7.5 (5)		4.7 (5)	5.7 (5)
<u>Ammonia (mg/L)</u>									
Residential:	0.1 (5) 0.9 (1) 0.5 (4)	0.1 (5)	0.3 (5)		<0.1 (5)		0.5 (5)	0.3 (5)	<0.1 (5) 0.42 (4)
Commercial:	1.1 (4)	1.4 (2) 0.35 (4) 0.38 (1)							<0.1 (5)
Industrial:	0.4 (5)	0.3 (5)	0.3 (5)	<0.1 (5)	<0.1 (5)	<0.1 (5)		<0.1 (5)	<0.1 (5)
<u>Phenols (mg/L)</u>									
Residential:	2.4 (5)	12.2 (5)	30.0 (5)		9.7 (5)		<0.4 (5)	8.6 (5)	6.2 (5)
Industrial:	1.2 (5)	9.4 (5)	2.6 (5)	8.7 (5)	7.0 (5)	7.4 (5)		8.7 (5)	24 (7)

Pollutant and Land Use	Roofs	Paved Parking	Paved Storage	Unpaved Parking/Storage	Paved Driveways	Unpaved Driveways	Dirt Walks	Paved Sidewalks	Streets
<u>Cadmium (µg/L)</u>									
Residential:	<4 (5) 0.6 (1)	2 (5)	<5 (5)		5 (5)		<1 (5)	<4 (5)	<5 (5)
Commercial:		5.1 (7) 0.6 (8)							<5 (5)
Industrial:	<4 (5)	<4 (5)	<4 (5)	<4 (5)	<4 (5)	<4 (5)		<4 (5)	<4 (5)
<u>Chromium (µg/L)</u>									
Residential:	<60 (5) <5 (4)	20 (5) 71 (4)	<10 (5)		<60 (5)		<10 (5)	<60 (5)	<60 (5) 49 (4)
Commercial:	<5 (4)	19 (7) 12 (8)							<60 (5)
Industrial:	<60 (5)	<60 (5)	<60 (5)	<60 (5)	<60 (5)	70 (5)		<60 (5)	<60 (5)
<u>Copper (µg/L)</u>									
Residential:	10 (5) <5 (4)	100 (5)	20 (5)		210 (5)		20 (5)	20 (5)	40 (5) 30 (4)
Commercial:	110 (4)	40 (2) 46 (4) 110 (7)							40 (5)
Industrial:	<20 (5)	480 (5)	260 (5)	120 (5)	40 (5)	140 (5)		30 (5)	220 (5)

Pollutant and Land Use	Roofs	Paved Parking	Paved Storage	Unpaved Parking/Storage	Paved Driveways	Unpaved Driveways	Dirt Walks	Paved Sidewalks	Streets
<u>Lead (µg/L)</u>									
Residential:	<40 (5) 30 (3) 48 (1) 17 (4)	250 (5)	760 (5)		1400 (5)		30 (5)	80 (5)	180 (5) 670 (4)
Commercial:	19 (4) 30 (1)	200 (2) 350 (3) 1090 (4) 146 (1) 255 (7) 54 (8)							180 (5)
Industrial:	<40 (5)	230 (5)	280 (5)	210 (5)	260 (5)	340 (5)		<40 (5)	560 (5)
<u>Zinc (µg/L)</u>									
Residential:	320 (5) 670 (1) 180 (4)	520 (5)	390 (5)		1000 (5)		40 (5)	60 (5)	180 (5) 140 (4)
Commercial:	310 (1) 80 (4)	300 (5) 230 (4) 133 (1) 490 (7)							180 (5)
Industrial:	70 (5)	640 (7)	310 (5)	410 (5)	310 (5)	690 (5)		60 (5)	910 (5)

(1) Bannerman, *et al.* 1983 (Milwaukee, WI) (NURP)

(3) Pitt 1983 (Ottawa)

(5) Pitt and McLean 1986 (Toronto)

(7) STORET Site #596296-2954843 (Huntington-Long Island, NY) (NURP)

(2) Denver Regional Council of Governments 1983 (NURP)

(4) Pitt and Bozeman 1982 (San Jose)

(6) STORET Site #590866-2954309 (Shop-Save-Durham, NH) (NURP)

Oversize table from Chapter 23.

Table 23.9

Pollutant and Land Use	Roofs	Paved Parking	Paved Storage	Unpaved Parking/Storage	Paved Drives	Unpaved Drives	Dirt Walks	Paved Side walks	Streets	Land-scaped	Un-developed	Freeway Paved Lane and Shoulders
Fecal Coliforms (#/100 ml)												
Residential:	85 (2) <2 (3) 1400 (4)	250,000 (4)	100 (4)		600 (4)			11,000 (4)	920 (3) 6,900 (4)	3300 (4)	5400 (2) 49 (3)	1500 (7)
Commercial	9 (3)	2900 (2) 350 (3) 210 (1) 480 (5) 23,000 (6)										
Industrial:	1600 (4)	8660 (6)	9200 (4)	18,000 (4)	66,000 (4)	300,000 (4)		55,000 (4)	100,000 (4)			

Pollutant and Land Use	Roofs	Paved Parking	Paved Storage	Unpaved Parking/Storage	Paved Drives	Unpaved Drives	Dirt Walks	Paved Side walks	Streets	Land-scaped	Un-developed	Freeway Lane and Shoulders
Fecal Strep (#/100 ml)												
Residential:	170 (2) 920 (3) 2200 (4) 17	190,000 (4)	<100 (4)		1900 (4)		1800 (4)		>2400 (3) 7300 (4)	43,000 (4)	16,500 (2) 920 (3)	2200 (7)
Commercial:	(2)	11,900 (2) >2400 (3) 770 (1) 1120 (5) 62,000 (6)										
Industrial:		7300 (4)	2070 (4)	8100 (4)	36,000 (4)	21,000 (4)		3600 (4)	45,000 (4)			
	690 (4)											
Pseudo, Aerug (#/100 ml)												
Residential:	30,000 (4) 50 (4)	1900 (4) 5800 (4)	100 (4) 5850 (4)	14,000 (4)	600 (4) 14,300 (4)	100 (4)	600 (4)	3600 (4)	570 (4) 6200 (4)	2100 (4)		
Industrial:												

(1) Bannerman, et al. 1983 (Milwaukee, WI) (NURP)

(2) Pitt 1983 (Ottawa)

(3) Pitt and Bozeman 1982 (San Jose)

(4) Pitt and McLean 1986 (Toronto)

(5) STORET Site #590866-2954309 (Shop-Save-Durham, NH) (NURP)

(6) STORET Site #596296-2954843 (Huntington-Long Island, NY) (NURP)

(7) Kobriger, et al. 1981 and Gupta, et al. 1977

Oversize tables from Chapter 24.

Table 24.1

	Total	Residential Filterable	Filterable (%)	Total	Commercial Filterable	Filterable (%)	Total	Industrial Filterable	Filterable (%)
Roof Runoff									
Solids (mg/L)	64	42	66 (1)				113	110	97 (3)
	58	45	77 (3)						
Phosphorus (mg/L)	0.054	0.013	24 (1)						
Lead (µg/L)	48	4	8 (1)						
Paved Parking									
Solids (mg/L)				240	175	73 (1)	490	138	28 (3)
				102	61	60 (4)			
				1790	138	8 (3)			
Phosphorus (mg/L)				0.16	0.03	19 (1)			
				0.9	0.3	33 (2)			
TKN (mg/L)				0.77	0.48	62 (5)			
Lead (µg/L)				146	5	3 (1)			
				54	8.8	16 (5)			
Arsenic (µg/L)				0.38	0.095	25 (5)			
Cadmium (µg/L)				0.62	0.11	18 (5)			
Chromium (µg/L)				11.8	2.8	24 (5)			

	Total	Residential Filterable	Filterable (%)	Total	Commercial Filterable	Filterable (%)	Total	Industrial Filterable	Filt. (%)
Paved Storage									
Solids (mg/L)				73	32	44 (3)	270	64	24 (3)

- (1) Bannerman, et al. 1983 (Milwaukee) (NURP)
- (2) Denver Regional Council of Governments 1983 (NURP)
- (3) Pitt and McLean 1986 (Toronto)
- (4) STORET Site #590866-2954309 (Shop-Save-Durham, NH) (NURP)
- (5) STORET Site #596296-2954843 (Huntington-Long Island, NY) (NURP)

Oversize table from Chapter 24.

Table 24.1

	Roof areas		Parking areas		Storage areas		Street runoff		Loading docks		Vehicle service areas		Landscaped areas		Urban creeks		Detention ponds	
Total samples	NF. ¹ 12	F. ² 12	NF. 16	F. 16	NF. 8	F. 8	NF. 6	F. 6	NF. 3	F. 3	NF. 5	F. 5	NF. 6	F. 6	NF. 19	F. 19	NF. 12	F. 12
Base neutrals (detection limit = 0.5 µg/L)																		
1,3-Dichlorobenzene (detection frequency = 20% N.F. and 13% F)																		
No. detected ³	3	2	3	2	1	1	1	1	0	0	3	2	3	2	2	0	1	1
Mean ⁴	52	20	34	13	16	14	5.4	3.3			48	26	29	5.6	93		27	21
Max. ⁵	88	23	103	26							72	47	54	7.5	120			
Min. ⁵	14	17	3.0	2.0							6.0	4.9	4.5	3.8	65			
Fluoranthene (detection frequency = 20% N.F. and 12% F)																		
No. detected	3	2	3	2	1	0	1	1	0	0	3	2	3	2	1	0	2	1
Mean	23	9.3	37	2.7	4.5	0	0.6	0.5			39	3.6	13	1.0	130		10	6.6
Max.	45	14	110	5.4							53	6.8	38	1.3			14	
Min.	7.6	4.8	3.0	2.0							0.4	0.4	0.7	0.7			6.6	
Pyrene (detection frequency = 17% N.F. and 7% F)																		
No. detected	1	0	3	2	1	0	1	1	0	0	3	2	2	0	1	0	2	1
Mean	28		40	9.8	8		1.0	0.7			44	4.1	5.3		100		31	5.8
Max.			120	20							51	7.4	8.2				57	
Min.			3.0	2.0							0.7	0.7	2.3				6.0	
Benzo(b)fluoranthene (detection frequency = 15% N.F. and 0% F)																		
No. detected	4	0	3	0	0	0	1	0	0	0	2	0	1	0	2	0	0	0
Mean	76		53				14				98		30		36			
Max.	260		160								110				64			
Min.	6.4		3.0								90				8.0			
Benzo(k)fluoranthene (detection frequency = 11% N.F. and 0% F)																		
No. detected	0	0	3	0	0	0	1	0	0	0	2	0	1	0	2	0	0	0
Mean			20				15				59		61		55			
Max.			1								103				78			
Min.			3.0								15				31			

	Roof areas		Parking areas		Storage areas		Street runoff		Loading docks		Vehicle service areas		Landscaped areas		Urban creeks		Detention ponds	
Total samples	NF. ¹ 12	F. ² 12	NF. 16	F. 16	NF. 8	F. 8	NF. 6	F. 6	NF. 3	F. 3	NF. 5	F. 5	NF. 6	F. 6	NF. 19	F. 19	NF. 12	F. 12
Benzo(a)pyrene (detection frequency = 15% N.F. and 0% F)																		
No. detected	4	0	3	0	0	0	1	0	0	0	2	0	1	0	2	0	0	0
Mean	99		40				19				90		54		73			
Max.	300		120								120				130			
Min.	34		3.0								60				19			
Bis(2-chloroethyl) ether (detection frequency = 12% N.F. and 2% F)																		
No. detected	3	1	2	0	0	0	1	0	0	0	1	1	1	0	1	0	1	0
Mean	42	17	20				15				45	23	56		200		15	
Max.	87	2	39															
Min.	20		2.0								6.0	4.9	4.5	3.8	65			
Bis(chloroisopropyl) ether (detection frequency = 13% N.F. and 0% F)																		
No. detected	3	0	3	0	0	0	0	0	0	0	2	0	1	0	2	0	0	0
Mean	99		130								120		85		59			
Max.	150		400								160				78			
Min.	68		3.0								74				40			
Naphthalene (detection frequency = 11% N.F. and 6% F)																		
No. detected	2	0	1	1	0	0	0	0	0	0	2	1	1	0	1	1	2	2
Mean	17		72	6.6							70	82	49		300	6.7	43	12
Max.	21										100						68	17
Min.	13										37						18	6.6
Benzo(a)anthracene (detection frequency = 10% N.F. and 0% F)																		
No. detected	1	0	3	0	0	0	0	0	0	0	2	0	1	0	1	0	0	0
Mean	16		24								35		54		61			
Max.			73								39							
Min.			3.0								31							

	Roof areas		Parking areas		Storage areas		Street runoff		Loading docks		Vehicle service areas		Landscaped areas		Urban creeks		Detention ponds	
Total samples	NF. ¹ 12	F. ² 12	NF. 16	F. 16	NF. 8	F. 8	NF. 6	F. 6	NF. 3	F. 3	NF. 5	F. 5	NF. 6	F. 6	NF. 19	F. 19	NF. 12	F. 12
Butylbenzyl phthalate (detection frequency = 10% N.F. and 4% F)																		
No. detected	1	0	2	1	0	0	0	0	0	0	2	2	1	0	1	0	1	0
Mean	100		12	3.3							26	9.8	130		59		13	
Max.			21								48	16						
Min.			3.3								3.8	3						
Pesticides (detection limit = 0.3 µg/L)																		
Chlordane (detection frequency = 11% N.F. and 0% F)																		
No. detected	2	0	2	0	3	0	1	0	0	0	1	0	0	0	0	0	0	0
Mean	1.6		1.0		1.7		0.8			0.8								
Max.	2.2		1.2		2.9													
Min.	0.9		0.8		1.0													
Metals (detection limit = 1µg/L)																		
Lead detection frequency = 100% N.F. and 54% F.																		
No. detected	12	1	16	8	8	7	6	4	3	1	5	2	6	1	19	15	12	8
Mean	41	1.1	46	2.1	105	2.6	43	2.0	55	2.3	63	2.4	24	1.7	20	1.4	19	1.0
Max.	170		130	5.2	330	5.7	150	3.9	80		110	3.4	70		100	1.6	55	1.0
Min.	1.3		1.0	1.2	3.6	1.6	1.5	1.1	25		27	1.4	1.4		1.4	<1	1	<1
Zinc detection frequency = 99% N.F. and 98% F.																		
No. detected	12	12	16	16	8	7	6	6	2	2	5	5	6	6	19	19	12	12
Mean	250	220	110	86	1730	22	58	31	55	33	105	73	230	140	10	10	13	14
Max.	1580	1550	650	560	13100	100	130	76	79	62	230	230	1160	670	32	23	25	25
Min.	11	9	12	6	12	3.0	4.0	4.0	31	4.0	30	11	18	18	<1	<1	<1	<1
Copper (detection frequency = 98% N.F. and 78% F)																		
No. detected	11	7	15	13	8	6	6	5	3	2	5	4	6	6	19	17	12	8
Mean	110	2.9	116	11	290	250	280	3.8	22	8.7	135	8.4	81	4.2	50	1.4	43	20
Max.	900	8.7	770	61	1830	1520	1250	11	30	15	580	24	300	8.8	440	1.7	210	35
Min.	1.5	1.1	10	1.1	10	1.0	10	1.0	15	2.6	1.5	1.1	1.9	0.9	<1	<1	0.2	<1

	Roof areas		Parking areas		Storage areas		Street runoff		Loading docks		Vehicle service areas		Landscaped areas		Urban creeks		Detention ponds	
Total samples	NF. 12	F. 12	NF. 16	F. 16	NF. 8	F. 8	NF. 6	F. 6	NF. 3	F. 3	NF. 5	F. 5	NF. 6	F. 6	NF. 19	F. 19	NF. 12	F. 12
Aluminum (detection frequency = 97% N.F. and 92% F)																		
No. detected	12	12	15	15	7	6	6	6	3	1	5	4	5	5	19	19	12	12
Mean (mg/L)	6.85	0.23	3.21	0.43	2.32	0.18	3.08	0.88	0.78	0.18	0.70	0.17	2.3	1.2	0.62	0.19	0.70	0.21
Max. (mg/L)	71.3	1.56	6.48	2.90	6.99	0.74	10.0	4.38	0.93		1.37	0.41	4.6	1.9	3.25	0.50	1.57	0.36
Min. (µg/L)	25	6.4	130	5.0	180	10	70	18	590		93	0.3	180	120	<5	<5	<5	<5
Cadmium (detection frequency = 95% N.F. and 69% F)																		
No. detected	11	7	15	9	8	7	6	5	3	3	5	3	4	2	19	15	12	9
Mean	3.4	0.4	6.3	0.6	5.9	2.1	37	0.3	1.4	0.4	9.2	0.3	0.5	0.6	8.3	0.2	2	0.5
Max.	30	0.7	70	1.8	17	10	220	0.6	2.4	0.6	30	0.5	1	1	30	0.3	11	0.7
Min.	0.2	0.1	0.1	0.1	0.9	0.3	0.4	0.1	0.7	0.3	1.7	0.2	0.1	0.1	<0.1	<0.1	0.1	0.4
Chromium detection frequency = 91% N.F. and 55% F.																		
No. detected	7	2	15	8	8	5	5	4	3	0	5	1	6	5	19	15	11	8
Mean	85	1.8	56	2.3	75	11	9.9	1.8	17		74	2.5	79	2.0	62	1.6	37	2.0
Max.	510	2.3	310	5.0	340	32	30	2.7	40		320		250	4.1	710	4.3	230	3.0
Min.	5.0	1.4	2.4	1.1	3.7	1.1	2.8	1.3	2.4		2.4		2.2	1.4	<0.1	<0.1	<0.1	<0.1
Nickel detection frequency = 90% N.F. and 37% F.																		
No. detected	10	0	14	4	8	1	5	0	3	1	5	1	4	1	18	16	11	8
Mean	16		45	5.1	55	87	17		6.7	1.3	42	31	53	2.1	29	2.3	24	3.0
Max.	70		130	13	170		70		8.1		70		130		74	3.6	70	6.0
Min.	2.6		4.2	1.6	1.9		1.2		4.2		7.9		21		<1	<1	1.5	<1

	Roof areas	Parking areas	Storage areas	Street runoff	Loading docks	Vehicle service areas	Landscaped areas	Urban creeks	Detention ponds
pH									
Mean	6.9	7.3	8.5	7.6	7.8	7.2	6.7	7.7	8.0
Max.	8.4	8.7	12	8.4	8.3	8.1	7.2	8.6	9.0
Min.	4.4	5.6	6.5	6.9	7.1	5.3	6.2	6.9	7.0
Suspended solids									
Mean	14	110	100	49	40	24	33	26	17
Max.	92	750	450	110	47	38	81	140	60
Min.	0.5	9.0	5.0	7.0	34	17	8.0	5.0	3.0

- 1) N.F.: concentration associated with a non-filtered sample.
- 2) F.: concentration after the sample was filtered through a 0.45 µm membrane filter.
- 3) Number detected refers to the number of samples in which the constituent was detected.
- 4) Mean values based only on the number of samples with a definite concentration reported (not on the total number of samples analyzed).
- 5) The minimum values shown are the lowest concentration detected; they are not necessarily the detection limit.

Oversize table from Chapter 24.

Table 24.2

Source Area	Total Solids (mg/L)	Suspended Solids (mg/L)	Dissolved Solids (mg/L)	COD Total (mg/L)	COD Particulate* (mg/Kg)	COD Dissolved (mg/L)	BOD ₅ , Total (mg/L)	BOD ₅ , Particulate* (mg/Kg)	BOD ₅ , Dissolved (mg/L)
Residential Roofs									
Sample Count	38	81	38	8	8	8	9	6	7
Average	112	36.7	60.8	78	590,000	30	19	140,000	9.6
COV**	1.12	2.07	1.20	1.34	0.72	0.68	0.49	0.6	0.54
Commercial Roofs									
Sample Count	19	34	19	6	6	6	9	4	6
Average	146	32.8	115	172	740,000	152.3	24	94,000	17.5
COV	0.66	1.25	0.85	0.66	1.05	0.69	0.78	0.94	0.84
Industrial Roofs									
Sample Count	45	42	42	34	32	34	n/a	n/a	n/a
Average	76	15.8	60.8	23	760,000	20	n/a	n/a	n/a
COV	0.40	1.7	0.54	0.60	0.88	0.60	n/a	n/a	n/a
Commercial Parking									
Sample Count	21	44	21	6	5	6	5	4	5
Average	246	130	62.7	77	330,000	39	10.5	28,000	7.5
COV	0.77	1.15	0.81	0.23	0.32	0.81	0.41	0.52	0.63
Industrial Parking Lots									
Sample Count	89	90	89	14	n/d	n/d	15	n/d	n/d
Average	1246	244	1002	120	n/d	n/d	18	n/d	n/d
COV	3	0.96	3	0.43	n/d	n/d	0.62	n/d	n/d
Driveways									
Sample Count	19	69	19	9	9	9	7	6	7
Average	350	154	111	146	300,000	91.8	16	32,000	7.71
COV	0.58	1.10	0.81	1.07	0.84	1.68	0.35	0.45	1.05
Small Landscape Areas									
Sample Count	13	40	13	4	4	4	2	1	1
Average	657	227	183	172.5	380,000	90.5	25	12,000	1.6
COV	0.62	1.25	1.10	0.23	0.63	0.50	0.55	n/a	n/a

*Particulate = (total constituent - dissolved constituent)/suspended solids **COV = coef of variance = mean/standard deviation

Source Area	Total Solids (mg/L)	Suspended Solids (mg/L)	Dissolved Solids (mg/L)	COD Total (mg/L)	COD Particulate* (mg/Kg)	COD Dissolved (mg/L)	BOD ₅ , Total (mg/L)	BOD ₅ , Particulate* (mg/Kg)	BOD ₅ , Dissolved (mg/L)
Commercial Streets									
Sample Count	50	75	50.0	16	14	14	12	11	12
Average	345	176	123	88	200,000	47.9	14	21,000	10.6
COV	0.89	1.17	1.05	0.45	0.84	0.63	0.51	0.81	0.54
Residential Streets									
Sample Count	32	131	32	5	3	4	4	2	4.0
Average	521	183	116	46.2	200,000	25	6.7	25,000	6.6
COV	1.16	1.7	0.92	0.39	0.78	0.75	0.95	0.24	0.97
Industrial Streets									
Sample Count	15	15	15	n/a	n/a	n/a	n/a	n/a	n/a
Average	1064	894	170	n/a	n/a	n/a	n/a	n/a	n/a
COV	0.58	0.69	0.64	n/a	n/a	n/a	n/a	n/a	n/a
Freeways									
Sample Count	11	66	11	n/a	n/a	n/a	n/a	n/a	n/a
Average	201	138	94.4	n/a	n/a	n/a	n/a	n/a	n/a
COV	0.51	1.17	0.39	n/a	n/a	n/a	n/a	n/a	n/a
Undeveloped Areas									
Sample Count	6	5	5	8	8	8	7	5	5
Average	260	16	186.2	87	720,000	69	26	67,000	20
COV	0.54	0.43	0.06	0.72	2.0	0.74	0.50	1.38	0.66

Source Area	P, Total (mg/L)	P, Part.* (mg/Kg)	P, Dis. (mg/L)	TKN (mg/L)	Kjeldahl N, Part.* (mg/Kg)	Kjeldahl N, Dis. (mg/L)	Nitrite + Nitrate N (mg/L)	Cd, Total (µg/L)	Cd, Part.* (mg/Kg)	Cd, Dis. (µg/L)
Residential Roofs										
Sample Count	87	76	82	7	7	7	8	21	5	14
Average	0.17	4600	0.07	1.1	18,000	0.80	0.68	0.54	9.0	0.15
COV	1.22	1.11	1.25	0.67	1.3	0.82	0.97	1.78	0.67	0.67
Commercial Roofs										
Sample Count	19	29	31	7	7	7	9.0	12	5	9
Average	0.18	9400	0.061	2.0	26,000	1.65	0.75	0.65	12.45	0.73
COV	0.67	1.24	1.09	0.56	1.55	0.73	0.86	1.03	1.00	1.06
Industrial Roofs										
Sample Count	9	9	9	n/a	n/a	n/a	n/a	4	1	4
Average	0.13	3400	0.021	n/a	n/a	n/a	n/a	0.30	1.56	0.28
COV	0.72	1.41	0.54	n/a	n/a	n/a	n/a	0.47	n/a	0.75
Commercial Parking Lots										
Sample Count	42	36	39	5	5	5	7	19	16	19
Average	0.2	1900	0.055	1.2	3900	0.58	0.4	0.95	4.65	0.48
COV	1.02	0.89	1.08	0.40	0.42	0.43	0.60	0.69	0.59	1.33
Industrial Parking Lots										
Sample Count	40	34	36	n/a	n/a	n/a	19	27	20	24
Average	0.39	1300	0.09	n/a	n/a	n/a	0.41	1.5	4.2	0.49
COV	0.58	0.66	1.1	n/a	n/a	n/a	0.62	0.53	0.55	1.11
Driveways										
Sample Count	69	66	65	9	9	9	9	19	14	14
Average	1	3400	0.290	2.6	9500	0.69	0.45	0.91	2.88	0.25
COV	1.24	0.79	1.76	0.73	0.69	0.90	1.03	1.06	0.79	0.74
Small Landscape Areas										
Sample Count	42	39	39	4	4	4	4	3	3	3
Average	2.2	7400	1.35	10.5	30,000	1.97	0.45	0.63	1.51	0.30
COV	1.08	1.23	1.63	0.53	0.69	0.52	0.53	0.40	0.69	0.99

Source Area	P, Total (mg/L)	P, Part.* (mg/Kg)	P, Dis. (mg/L)	TKN (mg/L)	Kjeldahl N, Part.* (mg/Kg)	Kjeldahl N, Dis. (mg/L)	Nitrite + Nitrate N (mg/L)	Cd, Total (µg/L)	Cd, Part.* (mg/Kg)	Cd, Dis. (µg/L)
Commercial Streets										
Sample Count	74.0	67	65	16	15	15	16	39	36	38
Average	0.31	1900	0.060	3.7	19,500	0.9	0.49	1.03	4.81	0.38
COV	1.11	0.72	1.21	2.18	2.95	0.70	0.56	0.67	0.74	1.54
Residential Streets										
Sample Count	132	127	127	5	4	4	5	14	9	9
Average	0.66	2800	0.298	1.0	5000	0.52	0.40	0.6	2.25	0.14
COV	1.39	0.83	1.78	0.15	0.65	0.19	0.35	0.85	0.80	0.37
Industrial Streets										
Sample Count	15	15	15	n/a	n/a	n/a	n/a	13	10	10
Average	1.3	1300	0.46	n/a	n/a	n/a	n/a	1.1	1.15	0.29
COV	0.37	0.59	0.77	n/a	n/a	n/a	n/a	0.82	0.88	0.60
Freeways										
Sample Count	21	20	20	10	10	10	10	21	11	11
Average	0.24	1700	0.08	1.3	7900	0.49	0.78	0.71	4.64	0.22
COV	0.56	0.60	0.93	0.32	0.64	0.45	0.83	0.36	0.34	0.39
Undeveloped Areas										
Sample Count	5	3	3	5	5	5	2	n/a	n/a	n/a
Average	0.08	400	0.01	1.1	1500	0.88	0.033	n/a	n/a	n/a
COV	0.30	0.49	0.82	0.09	0.70	0.10	0.24	n/a	n/a	n/a

Source Area	Cr, Total (µg/L)	Cr, Part.* (mg/Kg)	Cr, Dis. (µg/L)	Cu, Total (µg/L)	Cu, Part.* (mg/Kg)	Cu, Dis. (µg/L)	Pb, Total (µg/L)	Pb, Part. * (mg/Kg)	Pb, Dis. (µg/L)
Residential Roofs									
Sample Count	n/a	n/a	n/a	34	28	29	23	21	21
Average	n/a	n/a	n/a	21	160	10.2	43	870	8.47
COV	n/a	n/a	n/a	1.60	1.32	1.37	2.19	0.77	1.52
Commercial Roofs									
Sample Count	n/a	n/a	n/a	18	12	13	13	13	14
Average	n/a	n/a	n/a	19	180	12.9	58	750	27.1
COV	n/a	n/a	n/a	0.81	1.01	1.17	1.06	0.53	1.40
Industrial Roofs									
Sample Count	n/a	n/a	n/a	43	n/a	n/a	4	4	4
Average	n/a	n/a	n/a	9	n/a	n/a	8.25	220	1.50
COV	n/a	n/a	n/a	0.57	n/a	n/a	0.30	1.09	0.0
Commercial Parking									
Lots									
Sample Count	13	11	14	19	18	19	19	18	19
Average	9.8	47	2.46	30	100	14.4	51.1	320	1.72
COV	0.81	0.40	0.83	0.81	0.69	0.89	0.81	0.35	0.35
Industrial Parking									
Lots									
Sample Count	27	12	13	41	33	34	25	11	11
Average	11	24	1.26	33	83	11.0	53	180	2.06
COV	0.84	0.42	0.75	0.50	0.48	1.05	0.49	0.46	1.14
Driveways									
Sample Count	9	2	2	19	17	17	19	19	8
Average	1.94	11	1.5	37	89	13.0	57	240	3
COV	0.47	0.01	0.00	1.02	1.04	0.74	1.3	0.81	0.55
Small Landscape									
Areas									
Sample Count	1	1	1	11	10	11	3	3	3
Average	19	20	1.5	12	14	7.4	54	250	2.83
COV	n/a	n/a	n/a	0.36	0.42	0.51	0.90	1.07	0.64

Source Area	Zn, Total (µg/L)	Zn, Part.* (mg/Kg)	Zn, Dis. (µg/L)	Fluoranthene, Total (µg/L)	Fluoranthene, Part.* (mg/kg)	Pyrene, Total (µg/L)	Pyrene, Part.* (mg/kg)
Residential Roofs							
Sample Count	34	5	6	10	10	10	10
Average	185	2900	278	0.22	6.7	0.15	4.7
COV	1.09	0.56	0.80	1.09	0.75	1.12	0.84
Commercial Roofs							
Sample Count	15	6	6	10.0	10.0	10.0	10.0
Average	322	3500	182	0.85	25	0.6	18
COV	0.54	0.95	0.92	1.21	0.70	1.27	0.72
Industrial Roofs							
Sample Count	44	n/a	n/a	n/a	n/a	n/a	n/a
Average	319	n/a	n/a	n/a	n/a	n/a	n/a
COV	1.49	n/a	n/a	n/a	n/a	n/a	n/a
Commercial Parking Lots							
Sample Count	20	7	7	7	7	7	6
Average	292	802	51	28	290	17	180
COV	0.91	0.58	0.42	0.77	0.77	0.80	0.67
Industrial Parking Lots							
Sample Count	26	17	19	26	26	26	26
Average	227.7	490	99.5	2.48	10	1.85	7.7
COV	0.67	0.47	1.25	0.74	0.57	0.79	0.57
Driveways							
Sample Count	19	19	15	6	6	6	6
Average	164	650	166	1.1	23	0.8	17
COV	0.79	0.48	0.48	0.9	2.21	0.94	2.21
Small Landscape Areas							
Sample Count	10	2	2	n/a	n/a	n/a	n/a
Average	67	160	34.0	n/a	n/a	n/a	n/a
COV	0.39	1.28	0.37	n/a	n/a	n/a	n/a

Source Area	Zn, Total (µg/L)	Zn, Part.* (mg/Kg)	Zn, Dis. (µg/L)	Fluoranthene, Total (µg/L)	Fluoranthene, Part.* (mg/kg)	Pyrene, Total (µg/L)	Pyrene, Part.* (mg/kg)
Commercial Streets							
Sample Count	50	48	37	35	35	35	35
Average	302	1150	60.2	5.0	25	3.4	17
COV	0.95	1.23	1.03	1.4	1.0	1.39	0.93
Residential Streets							
Sample Count	32	26	11	13	13	12	12
Average	151	350	45.0	1.3	9.6	0.9	6.5
COV	0.71	0.55	0.39	1.20	0.78	1.08	0.78
Industrial Streets							
Sample Count	15	15	15	n/a	n/a	n/a	n/a
Average	593	540	167	n/a	n/a	n/a	n/a
COV	0.48	0.42	0.51	n/a	n/a	n/a	n/a
Freeways							
Sample Count	57	21	21	11	11	11	11
Average	233	1330	22.6	1.1	11	0.71	6.6
COV	0.78	0.36	0.42	1.0	0.77	0.94	0.63
Undeveloped Areas							
Sample Count	n/a	n/a	n/a	n/a	n/a	n/a	n/a
Average	n/a	n/a	n/a	n/a	n/a	n/a	n/a
COV	n/a	n/a	n/a	n/a	n/a	n/a	n/a